Discover Great Sound BLU Series



There once was a time when great home theater experiences were reserved for the elite. Speakers capable of filling the room with high-end sound, creating the effect of actually being in the middle of the action, were not practical for every budget. But with the introduction of the BLU Series, TruAudio has proven once and for all that great home theater experiences don't have to cost a fortune. You too can have a home theater to brag about, without breaking your bank!

The BLU Series was meticulously designed to provide the sound of a high-end, expensive speaker at a fraction of the cost. Its three-way design with side-firing woofer offers detailed, but not too heavy, audio. Its crossover was simplified, weeding out unnecessary components to produce cleaner, more accurate sound. Driver materials, cabinet size, cabinet design – each element was specifically chosen to create a speaker that lives up to TruAudio's highest standards.

TruAudio's BLU Series is being praised as the most versatile and affordable floor standing loudspeakers on the market. From a small bookshelf music system to a rumbling home theater - surround yourself in sound that will make your friends BLU with envy.





BLU Series ■ Product Specs

BLU-6L & BLU-6R



Woofer: 8" polypropylene Midrange: 6 1/2" aluminum 1" aluminum Tweeter: Power: 5-150 watts Impedance: 8 ohms 40-20k Hz Frequency Response: 90 dB Sensitivity: Cabinet Finish: PVC wood look Colors Available: Natural & black Grill Type: Black cloth Finish Dimensions: 40 1/4" (1022.35 mm) H, 9 1/4" (234.95 mm) W, 12 5/8" (320.5 mm) D

BLU-5C

Woofers:



Tweeter: 3/4" aluminum 5-120 watts Power: Impedance: 8 ohms Frequency Response: 61-20k Hz 90 dB Sensitivity: Cabinet Finish: PVC wood look Colors Available: Natural & black Grill Type: Black cloth Finish Dimensions: 6 3/4" (171.45 mm) H, 22 1/4" (565.15 mm) W, 7 1/4" (184.15 mm) D

Dual 5 1/4" aluminum

BLU-5S



Woofer: 5 1/4" aluminum 3/4" aluminum Tweeter: Power: 5 - 120 watts Impedance: 8 ohms 67-20k Hz Frequency Response: Sensitivity: 89 dB Cabinet Finish: PVC wood look Colors Available: Black, natural Grill Type: Black cloth Finish Dimensions: 13" (330.2 mm) H, 6 3/4" (171.45 mm) W, 7 1/4" (185.15 mm) D

BLU-5SUR



Woofers: Dual 5 1/4" aluminum Tweeters: Dual 3/4" aluminum 5 - 120 watts Power: Impedance: 8 ohms Frequency Response: 68-20k Hz Sensitivity: 89 dB Cabinet Finish: PVC wood look Colors Available: Black Grill Type: Black cloth Finish Dimensions: 12 5/8" (320.5 mm) H, 9 1/2" (241.3 mm) W, 7 1/2" (190.5 mm) D

B-631



Bipole in-wall speakers Speaker Type: Woofer: 6 1/2" aluminum Dual 2" aluminum Midranges: Dual 1" aluminum Tweeters: 5 - 100 watts Power: Impedance: 8 ohms 53-20k Hz Frequency Response: 90 dB Sensitivity: EQ Adjustments: Tweeter & Woofer +3, 0, -3 Grill Type: Micromesh Finish Dimensions: 12 5/8" (320.5 mm) H, 9 1/8" (231.8 mm) W,

3 1/2" (88.9 mm) D 11 5/8" (295.1 mm) H, Cutout Dimensions: 8" (203.2 mm) W

■ Subwoofers (sold separately)





Speaker Type: Enclosure Design: Driver: Power: Frequency Response, Low Pass: Frequency Response, LFE: Sensitivity: Crossover: Input:

Grill Type: Cabinet Dimensions:

Colors Available:

Front-firing, front-ported 8" cellulose composite 100 watt internal amplifier 37 - 150 Hz. (+/-3 dB) 20 - 380 Hz. (+/-3 dB) 130mV @ 100W 60 – 180 Hz. continuously variable low pass Line level RCA, speaker level MDF frame w/ black speaker cloth 15" (381 mm) H (including feet), 11 1/4" (285.75 mm) W, 14 1/2" (368.3 mm) D

(including grill and amp)

Black, lightly textured

SUB-10



Powered subwoofer Front-firing, front-ported 10" cellulose composite 150 watt internal amplifier 33 - 150 Hz. (+/-3 dB) 20 - 380 Hz. (+/-3 dB) 131mV @ 100W 50 - 180 Hz. continuously variable low pass Line level RCA, speaker level MDF frame w/ black speaker cloth 17 3/4" (450.85 mm) H (including feet), 13" (330.2 mm) W, 16 1/4" (412.75 mm) D (including grill and amp) Black, lightly textured

SUB-12

Powered subwoofer

Front-firing, front-ported



12" cellulose composite 200 watt internal amplifier 30 - 150 Hz. (+/-3 dB) 20 - 380 Hz. (+/-3 dB) 151mV @ 100W 50 – 180 Hz. continuously variable low pass Line level RCA, speaker level MDF frame w/ black speaker cloth 19 3/4" (501.65 mm) H (including feet), 15" (381 mm) W, 18 1/2" (469.9 mm) D (including grill and amp) Black, lightly textured



439 North 3050 East St. George, Utah 84790 phone: 888.858.1555 fax: 435.251.9815 email: sales@truaudio.com web: www.truaudio.com