



# DATA SHEET

## Cool-stick

### General Description

Developed specifically for ventilating flat panel displays that have been recessed into walls. Sixteen 50mm fans wired in 2 groups provide a high level of airflow and 100% redundancy. Each fan group has its own power supply and thermal switch; any failure results in at least 50% of airflow being maintained. Includes adjustable mounting brackets.



### Features

- ✍ Redundancy to protect expensive displays
- ✍ Thermal switches automate operation
- ✍ Extremely low noise
- ✍ 1 year parts and labor warranty

### Specifications

Parameter	Value	Units
<b>Air Flow</b>	<b>60 (free air); 15 (typical)</b>	<b>CFM</b>
<b>Noise level</b>	<b>19</b>	<b>dBA</b>
<b>Dimensions</b>	<b>36l x 3/4" x 2 3/8"</b>	<b>Inches</b>
	<b>92 x 2 x 6</b>	<b>cm</b>
<b>Power consumption</b>	<b>4 (each fan group)</b>	<b>Watts</b>
<b>Weight</b>	<b>4/1.8</b>	<b>Lbs/kg</b>
<b>Part number</b>	<b>00-701-01</b>	

Cool-stack and the ATM logo are registered trademarks of Active Thermal Management. All features and specifications subject to change without notice.