

Overview

The Component-Composite Video ProAV Balun (500056-Pro) allows one component video (YPbPr or RGB) signal plus one composite video signal to be transmitted via one Cat5e/6 twisted pair cable for more cost-efficient cabling.

The 500056-Pro features Ethercon™ RJ45, ruggedized cast aluminum enclosure and built-in 12-inch (30cm) heavy duty AV cable leads for the demanding professional environment. The 500056-Pro may be used in pairs or in conjunction with other MuxLab component video baluns.

Applications

Rental & staging
Mobile production
Venues



Features


- Supports 1080i/p up to 500 ft (152m) via Cat5e/6
- Supports composite video on fourth twisted pair
- Ethercon™ RJ45 connector for cable strain relief
- Ruggedized cast aluminum enclosure
- Heavy-duty 12-inch (30cm) built-in cable leads
- Compatible with 500056
- Lifetime warranty

| Specifications | |
|---|---|
| Environment | Component Video (YPbPr), RGB Video (sync on green). 480i/p, 720p, 1080i/p. Line level Composite Video (NTSC, PAL, SECAM). |
| Devices | DVD players, satellite receivers, plasma displays, projectors, monitors, up-converters, amplifiers, switchers, home theatre and other equipment supporting HDTV component video and/or Composite Video. |
| Transmission | Transparent to the user. |
| Bandwidth | Video: 60 MHz, 3 dB roll off. Composite Video: DC to 8 MHz |
| Maximum Input | 1.1Vp-p |
| Insertion Loss per pair | Component: Less than 3 dB per pair over the frequency range. Composite: Less than 2 dB per pair over the frequency range. |
| Return Loss | Greater than 15 dB over the frequency range |
| Common Mode Rejection | Component: -55 dB max. Composite: Greater than 40 dB @ 8 MHz |
| Max. Distance – Cat 5E/6 UTP & STP | 480i/p: 1,000 ft (305m). 720p and 1080i/p: 500 ft (152m). Composite Video: 2,200 ft (670m). |
| Cable – Cat5/6 UTP/STP | 24 gauge or lower solid copper twisted pair wire. Impedance: 100 ohms at 1 MHz. Maximum capacitance: 20 pf/foot. Attenuation: 6.6 dB/1000 ft at 1 MHz |
| Cable – Coax | Impedance: 75 ohms at 1 MHz |
| Connectors | Three (3) RCA-M connectors: Green (Y), Blue (Pb), Red (Pr) One (1) RCA-F connector for Composite Video Ethercon RJ45S for twisted pair |
| Pin Configuration <i>Reverse polarity sensitive</i> | Red (Pr): Pins 7 [R] & 8 [T] Green (Y): Pins 3 [R] & 6 [T] Blue (Pb): Pins 1 [R] & 2 [T] Composite Video: Pins 4 [R] & 5 [T] |
| Temperature | Operating: 0° to 55°C. Storage:-20° to 85°C. Humidity: up to 95% |
| Enclosure | Cast aluminium |
| Dimensions | 2.75" x 2.64" x 1.975" (6.99cm x 6.71cm x 5.02cm) plus 12" (30cm) cable leads |
| Weight | .542lb (245.85g) |
| Regulatory | FCC, CE, RoHS. |
| Warranty | Lifetime |
| Order Information | 500056-Pro Component/Composite Video ProAV Balun |

Ethercon is a trademark of Neutrik® AG

Component-Composite Video ProAV Balun 500056-Pro

Typical Application



Head Office

8495 Dalton Road, Mount Royal, Quebec, Canada, H4T 1V5

Tel: 514-905-0588 Fax: 514-905-0589

Toll-free: 877-689-5228

E-mail: videoease@muxlab.com

URL: www.muxlab.com